



## VXI120 Variable Voltage Interface for VXI

### Features

- 192 Channel Differential TTL / TLL interface
- 50MHz transfer rate
- Six user loadable FPGAs for automated data processing
- Single slot VXI form factor
- 32-bit VXI/VME bus interface
- Integrated over-voltage protection on all lines

### Summary

Phillips' VXI120 configurable Differential TTL /TTL module interface card is an intelligent digital interface capable of supporting development and validation testing. The VXI120 has 6 on-board field programmable gate arrays (FPGAs) to support bus emulation, protocol simulation, test algorithm generation and other data conversion functions.

The user can configure (on-the-fly) the direction and type of I/O for each pin. The VXI120 provides a very flexible interface with independent high and low thresholds that can be set using two 14-bit DACs for each channel. When in input mode, the FPGAs can detect when the signal is above, below, or in between the thresholds. When in output mode, high and low output levels be set as well. High and low ranges can each be set to any levels between -15V and +15V. Built-in diodes protect each channel from overvoltage conditions, and current limiting resistors protect against overcurrent conditions.

The VXI120's six ACEX1K100s have capacity and memory to support complex operations decoupled from the VXI bus. This allows the VXI120 to operate at high speed without being interrupted by the host controller.

The user can program the FPGAs through the VXI interface, or via on-board EPROM so the board is automatically loaded. Example FPGA code and driver source code are provided with the VXI120.

The VXI120 has a VME32 compatibility mode that allows high speed operation with a VME style real-time host controller instead of a VXI host controller.

Custom versions of the VXI120 are available to our customers. Please contact the factory for further information.

### Specifications

Channels:	192 user-defined I/O, direction control for each, two I/O can be combined to operate as a differential pair
Clock Rate:	50MHz max
Output:	H>2V into 500hms, L<0.2V Sink 20mA Source 20mA
Input:	H>2V, L<0.8V
Termination:	120Ω (differential mode)
OVP:	Transient suppression on all lines
Clocks:	On-board crystal, DDS
FPGA:	ACEX1K100
Connectors:	Six VHDCI 68-pin female connectors
Power:	+5V @ 6.0A max

### Ordering Information

#### Hardware

335-4113

*VXI120 192 channel differential TTL / TTL*

335-4112

*VXI120 128 channel differential TTL / TTL*

335-4111

*VXI120 64 channel differential TTL / TTL*

#### Software

VXI-API-QNX

*QNX® software support package*

VXI-API-WIN

*Windows® DLL software package*

#### Accessories

TP-DIN68S

*Termination panel, VHDCI receptacle*

CBSCSI-6803MM

*Cable, shielded, 3-ft, VHDCI plug at both ends*